

DATA SHEET



Unit 21 Priory Industrial Park
Airspeed Road
Christchurch
Dorset
BH23 4HD

Tel: 01425 278011

Fax: 01425 278012

www.deltarubber.co.uk

deltasales@deltarubber.co.uk

DR-C20 Black Neoprene Rubber 65° shore A

Description

DR-C20 Black commercial quality Neoprene 65° sh A material.

- Thickness: 1.0mm to 25mm (other thickness on request)
- Sheet size: 1.4m wide x 5,10 or 20m rolls
- Finish: Plate Finish
- Cutting: Standard Press- Tools

Technical Information

Material:	Chloroprene/SBR CQ Grade
Application:	General Purpose, Water/UV/Oil/Fuel Resistant
Thickness:	1.0, 1.5, 2, 3, 4, 5, 6, 8, 10, 12, 15, 20, 25mm
Colour:	Black
Cloth/Plate Finish:	Plate
Density [specific gravity]:	1.4 g/cm ³
Hardness [Degrees Shore A]:	60° ± 5°
Tensile Strength [Mpa]:	5.0 min
Elongation at break :	300 %
Minimum Temperature :	-20°C
Maximum temperature:	+110°C
Compression Set :	35%
Tear resistance (kg/cm):	20



Certificate No: GB08/75575