

Product Data Sheet



DRE80 EPDM Rubber sheet

A general purpose medium grade 65/70°sh EPDM/SBR, suitable for low pressure pipe seals, gaskets, weatherstrip, etc. Excellent water, ozone & UV resistant properties, vegetable oils, acids, aqueous chemicals, steam. Also has good mechanical properties and abrasion resistance. WRAS approved potable water grades are also available.

Unit 21 Priory Industrial Park
Airspeed Road
Christchurch
Dorset
BH23 4HD
Tel: 01425 278011
Fax: 01425 278012
www.deltarubber.co.uk
deltasales@deltarubber.co.uk

PROPERTY

Base Polymer

Colour

Hardness

Specific Gravity

Tensile Strength

Elongation at break

Tear Strength

Compression Set (22hrs @ 70°C)

Abrasion Resistance

Temperature Range

TYPICAL VALUES

Ethylene Propylene Diene Monomer

Black

70° +/- 5° Shore A

1.4 gm/cm³

5.0 Mpa

300%

12 kN/m

49%

490

-35°C to +120°C

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable, but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied.



Cert No. GB08/75575

This product is REACH, RoHS, PAH & CE Compliant