

SPECIFICATION SHEET



DSM175 Fuel – grade Nitrile/PVC Rubber

Unit 21 Priory Industrial Park
Airspeed Road
Christchurch
Dorset
BH23 4HD
Tel: 01425 278011
Fax: 01425 278012
www.deltarubber.co.uk
deltasales@deltarubber.co.uk

Description

This material is a commercial grade high fuel resistant Nitrile/PVC 65°shoreA rubber compounded for use in a wide range of gasket & similar applications.

- **Material Profile: See Below**
- **Thickness: 1.5mm to 6mm (other thickness on request)**
- **Sheet size: 1.4m wide x 0m rolls**
- **Finish: Smooth**
- **Cutting: Standard Tools**

Technical Information

Material:	NBR/PVC, Nitrile CQ Rubber
Application:	Oil-based products/ fuel resistant / General purpose
Thickness:	1.5mm, 3mm, 6mm
Colour:	Black
Cloth/Plate Finish:	Plate / Plate
Compound:	NBR/PVCSBR
Density [specific gravity]:	1.25
Hardness [Degrees Shore A]:	65° ± 5°
Tensile Strength [Mpa]:	6.0
Elongation at break %:	250 %
Minimum Temperature :	-20°C
Maximum temperature:	+110°C
Compression Set 70°, 22hrs:	40%

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable, but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied.



Certificate No: GB08/75575

This product is REACH, RoHS, PAH & CE Compliant.

Directors: Martin Bailey, Jonathan Fisher

Registered in England No: 6033135

VAT No: GB 899 1951 52