

# BS2752-C40 Neoprene Rubber



## DRC24 DATA SHEET

**DELTA RUBBER LIMITED**

Unit 21 Priory Industrial Park, Airspeed Road  
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

### Description

DRC24 Black BS2752-C40 specification high quality Neoprene 40° shore A material, suitable for a wide range of applications with excellent general mechanical properties and resistance to oils & greases, water, ozone, mild chemicals, acids etc.

### Technical Information

|                             |  |
|-----------------------------|--|
| Material:                   | Chloroprene BS specification grade           |
| Application:                | General Purpose, Water/UV/Oil/Fuel Resistant |
| Thickness:                  | 0.5,1,1.5,2,3,5,6mm                          |
| Colour:                     | Black  |
| Cloth/Plate Finish:         | Plate  |
| Density [specific gravity]: | 1.25   |
| Hardness [Degrees Shore A]: | 40° ± 5°                                     |
| Tensile Strength [MPA]:     | 9 min  |
| Elongation at Break:        | 450%   |
| Minimum Temperature:        | -30°C  |
| Maximum Temperature:        | +120°C                                       |
| Compression Set:            | 30%  |
| Tear Resistance (kg/cm)     | N/A  |

#### Thickness

0.5mm-6mm  
(other thicknesses on request)

#### Sheet Size

1.4m wide x 5,10m rolls

#### Finish

Plate

#### Cutting

Standard Press Tools



# BS2752-C50 Neoprene Rubber



**DRC25**

## DATA SHEET

**DELTA RUBBER LIMITED**

Unit 21 Priory Industrial Park, Airspeed Road  
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

### Description

DRC25 Black BS2752-C50 specification high quality Neoprene 50° shore A material, suitable for a wide range of applications with excellent general mechanical properties and resistance to oils & greases, water, ozone, mild chemicals, acids etc.

### Technical Information

|                             |  |
|-----------------------------|--|
| Material:                   | Chloroprene BS specification grade           |
| Application:                | General Purpose, Water/UV/Oil/Fuel Resistant |
| Thickness:                  | 0.5,1,1.5,2,3,5,6mm                          |
| Colour:                     | Black  |
| Cloth/Plate Finish:         | Plate  |
| Density [specific gravity]: | 1.35   |
| Hardness [Degrees Shore A]: | 50° ± 5°                                     |
| Tensile Strength [MPA]:     | 12 min                                       |
| Elongation at Break:        | 400%   |
| Minimum Temperature:        | -30°C  |
| Maximum Temperature:        | +120°C                                       |
| Compression Set:            | 30%  |
| Tear Resistance (kg/cm)     | N/A  |

#### Thickness

0.5mm-6mm

(other thicknesses on request)

#### Sheet Size

1.4m wide x 5,10m rolls

#### Finish

Plate

#### Cutting

Standard Press Tools



# BS2752-C60 Neoprene Rubber



## DRC26 DATA SHEET

**DELTA RUBBER LIMITED**

Unit 21 Priory Industrial Park, Airspeed Road  
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

### Description

DRC26 Black BS2752-C60 specification high quality Neoprene 60° shore A material, suitable for a wide range of applications with excellent general mechanical properties and resistance to oils & greases, water, ozone, mild chemicals, acids etc.

### Technical Information

|                             |  |
|-----------------------------|--|
| Material:                   | Chloroprene BS specification grade           |
| Application:                | General Purpose, Water/UV/Oil/Fuel Resistant |
| Thickness:                  | 0.5,1,1.5,2,3,5,6mm                          |
| Colour:                     | Black  |
| Cloth/Plate Finish:         | Plate  |
| Density [specific gravity]: | 1.40   |
| Hardness [Degrees Shore A]: | 60° ± 5°                                     |
| Tensile Strength [MPA]:     | 13 min                                       |
| Elongation at Break:        | 350%   |
| Minimum Temperature:        | -30°C  |
| Maximum Temperature:        | +120°C                                       |
| Compression Set:            | 25%  |
| Tear Resistance (kg/cm)     | N/A  |

#### Thickness

0.5mm-6mm

(other thicknesses on request)

#### Sheet Size

1.4m wide x 5,10m rolls

#### Finish

Plate

#### Cutting

Standard Press Tools



# BS2752-C70 Neoprene Rubber



## DRC27 DATA SHEET

**DELTA RUBBER LIMITED**

Unit 21 Priory Industrial Park, Airspeed Road  
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

### Description

DRC27 Black BS2752-C70 specification high quality Neoprene 70° shore A material, suitable for a wide range of applications with excellent general mechanical properties and resistance to oils & greases, water, ozone, mild chemicals, acids etc.

### Technical Information

|                             |  |
|-----------------------------|--|
| Material:                   | Chloroprene BS specification grade           |
| Application:                | General Purpose, Water/UV/Oil/Fuel Resistant |
| Thickness:                  | 0.5,1,1.5,2,3,5,6mm                          |
| Colour:                     | Black  |
| Cloth/Plate Finish:         | Plate  |
| Density [specific gravity]: | 1.40   |
| Hardness [Degrees Shore A]: | 70° ± 5°                                     |
| Tensile Strength [MPA]:     | 13 min                                       |
| Elongation at Break:        | 300%   |
| Minimum Temperature:        | -30°C  |
| Maximum Temperature:        | +120°C                                       |
| Compression Set:            | 25%  |
| Tear Resistance (kg/cm)     | N/A  |

#### Thickness

0.5mm-6mm  
(other thicknesses on request)

#### Sheet Size

1.4m wide x 5,10m rolls

#### Finish

Plate

#### Cutting

Standard Press Tools

