

# Black EPDM Rubber

## DRE-80 DATA SHEET



**DELTA RUBBER LIMITED**

Unit 21 Priory Industrial Park, Airspeed Road  
Christchurch, Dorset, BH23 4HD

t: 01425 278011 [www.deltarubber.co.uk](http://www.deltarubber.co.uk) [deltasales@deltarubber.co.uk](mailto:deltasales@deltarubber.co.uk)

### Description

A general-purpose medium grade 65/70° EPDM/SBR, suitable for low pressure pipe seals, gaskets, weatherstrip etc. Excellent water, ozone & UV resistant properties. Also has good mechanical properties and abrasion resistance. WRAS approved portable water grades also available.

### Technical Information

Base Polymer:	Ethylene Propylene Diene Monomer
Colour:	Black
Harness:	70° +/- 5° Shore A
Specific Gravity:	1.4 gm/cm <sup>3</sup>
Tensile Strength:	5.0 Mpa
Elongation at Break:	300%
Tear Strength:	12 kN/m
Compression Set (22hrs @ 70°)	49%
Abrasion Resistance:	490
Temperature Range:	-35°C to +120°C

#### Thickness

1.0mm – 12mm  
(other thicknesses on request)

#### Sheet Size

1.4m wide x 5, 10m rolls

#### Cutting

Standard Press Tools

