



## DA325 PVC/Nitrile Closed-cell Foam

Unit 21 Priory Industrial Park  
Airspeed Road  
Christchurch  
Dorset  
BH23 4HD  
Tel: 01425 278011  
Fax: 01425 278012

[www.deltarubber.co.uk](http://www.deltarubber.co.uk)  
[deltasales@deltarubber.co.uk](mailto:deltasales@deltarubber.co.uk)

### Product Description

A general purpose closed-cell soft foam for a wide range of sealing, noise and thermal insulating & gap-filling applications. Also used in electrical cable tray installation. Withstands weathering & exposure to oil, & grease. Also meets BS476 Class 0 fire retardancy requirements. Available with self-adhesive backing.

### Specification

Density	55-70 kg/m <sup>3</sup>	BS EN ISO 845
Colour	Black-Grey	
Thickness	3mm to 50mm	
Thermal Conductivity	0.037W/mK	BS874 pt2 1986
Surface Spread of Flame	Class 1	BS476 pt7 1987
Building Regs 1991 (Fire Safety)	Class 0	BS476 pt6 1989
Operating temperature	-50°C to 116°C	
Water Vapour Permeability	μ≥5000	BS4370 pt 2 1973
Water Absorption (by vol 28 days)	0.9% average	
Noise Reduction	Up to 30db(A)	

All data and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is given or implied in respect of information or recommendations. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties.



Cert No. GB08/75575